

## Immersion heater for floor standing boilers G 1½”



Immersion heater supplied with bipolar thermostat with safety cut-out. The thermostat includes an operation indicating lamp and a protective cover composed of flame retardant material (polyamide), with cable gland to grip the power cord. The heater is made of stainless-steel grade AISI 316L (EN 1.4404) or nickel alloy INCOLOY 825 (EN 2.4858). INCOLOY 825 offers high endurance to corrosion. Power ranging from 1,2 to 4 kW – 230V, on G 1½” thread.

PRODUCT CODE	kW - 230 V	ALLOY
21110052	1.2	AISI 316L
21110044	1.5	AISI 316L
21110053	2.0	AISI 316L
21110034	2.5	AISI 316L
21110114	3.0	AISI 316L
21110270	3.0	INCOLOY 825*
21110033	3.5	AISI 316L
21110128*	3.7	AISI 316L
21110115	4.0	AISI 316L

\* inactive zone 100mm

**WARNING:** The product must be used in conjunction with a magnesium anode to ensure cathodic protection. Alternatively, product failure is expected shortly after its installation.

This leaflet has been drawn up for information purposes only and is not binding to our company as to the appearance, the technical specifications of the product or in any other way. For specified information please contact our company: [info@drall.gr](mailto:info@drall.gr)